



DIRECTIONS:
PLEASE INDICATE
COMPLIANCE FOR EACH ITEM
BY CHECKING THE
CORRESPONDING BOX.

THIS FORM MUST BE SUBMITTED TO THE
SUPERONE SCRUTINEERS PRIOR TO ENTERING THE
CIRCUIT FOR YOUR FIRST SESSION (WETHER THAT
BE PRACTICE, QUALIFYING, HEAT OR FINALS).
FAILURE TO DO SO MAY RESULT IN NOT BE
ALLOWED ON THE CIRCUIT.

DRIVER NAME _____
NAME

Parent/Guardian if under
18 years.

MECHANIC _____
NAME

CIRCUIT _____

DATE _____

CLASS _____

RACE _____

NUMBER _____

SIGNATURE:

PRINT NAME:

BY SIGNING/FILLING OUT THIS FORM – I PRESENT THIS
KART AND DOCUMENT AND CERTIFY THAT ALL ITEMS ON
THIS FORM HAVE BEEN COMPLETED, VERIFIED AND WILL
BE MAINTAINED THROUGHOUT THE DURATION OF THE
EVENT.

ITEMS THAT NEED TO BE SECURED BY NYLOCK OR K NUT

STEERING ASSEMBLY

- STEERING WHEEL TO HUB BOLTS
- STEERING HUB TO SHAFT BOLT
- STEERING SHAFT TO CHASSIS
- TIE ROD END BOLTS
- KINPIN BOLTS
- SPINDLE NUT ATTACHING WHEEL
- WHEEL TO HUB

BREAKING SYSTEM

- PEDAL PIVOT TO CHASSIS
- ACTUATING ROD AND CABLE ENDS
- MASTER CYLINDER TO CHASSIS BOLTS
- CALIPER(S) TO CHASSIS BOLTS
- PAD RETAINING RODS
- BRAKE DISCS TO HUB (METAL LOCKNUTS
ONLY)

BODYWORK

- BODYWORK MOUNTED AS INTENDED BY
MANUFACTURER

FUEL: MANDATORY RATIO

- I CAN CONFIRM I AM USING THE
DEDICATED PUMP FUEL

GENERAL SAFETY REQUIREMENTS WHICH MUST BE ADHERED TO:

- PUSH BACK BUMPER BRACKETS IN PLACE AND
READY FOR BUMPER INSPECTION AND
INSTALLATION AT GRID
- CK-SPECIFICATION BRAKE SAFETY CABLE WITH A
MINIMUM DIAMETER OF 1.8MM
- BRAKE FUNCTIONALITY TEST – SUFFICIENT
FORCE APPLIED TO BRAKE PEDAL SHALL RESULT
IN ALL APPLICABLE WHEELS BEING UNABLE TO
TURN
- HELMET MEETS LATEST SUPER ONE RULES
- PLEASE ENTER THE HELMET RATING FROM THE
INSIDE OF YOUR HELMET HERE: _____
- SEAT MOUNTING TABS AND STRUTS
IMPLEMENTED PER INTENT OF CHASSIS
MANUFACTURER
- FUNCTIONAL FUEL AND WATER RECOVERY
SYSTEM
- CORRECT KART NUMBER, COLOUR AND
BACKGROUND (4 LOCATIONS) AS APPROVED IN
REGISTRATION
- REAR PROTECTION MEETS CURRENT SUPERONE
RULES, WEIGHT(S) (BALLAST):
 - WEIGHT(S) SECURED BY TWO (2 X 8MM BOLTS)
 - DOUBLE NUTTED
- RECOMMENDED: METAL OR 3MM PLASTIC
SEAT/SEAT STRUT REINFORCEMENT WASHERS –
MIN 35MM DIAMETER
- STARTER BATTERIES LABELLED WITH KART
NUMBER AND CLASS
- AUXILLIARY THROTTLE CABLE RETURN SPRING